

SUBMITTAL DATA

Flexmaster U.S.A.® Straight Collar SOG

SHEET METAL FITTINGS



The Flexmaster U.S.A.® Straight Collar with stick on gasket (FL-SOG) is manufactured from 26 gauge, or heavier, G-90 galvanized steel to meet SMACNA and UMC Standards for commercial construction.

The FL-SOG is manufactured with a 1" formed on flange and Stick on Gasket to provide air-tight installation.

The FL-SOG should be installed using SMACNA installation standards.

Order Size	Diameter	Length w/ Damper	Length w/o Damper
4"	3 7/8"	6 1/2"	3 1/2"
5"	4 7/8"	6 1/2"	3 1/2"
6"	5 7/8"	6 1/2"	3 1/2"
7"	6 7/8"	6 1/2"	3 1/2"
8"	7 7/8"	6 1/2"	3 1/2"
9"	8 7/8"	6 1/2"	3 1/2"
10"	9 7/8"	6 1/2"	3 1/2"
12"	11 7/8"	6 1/2"	3 1/2"
14"	13 7/8"	6 1/2"	3 1/2"
15"	14 7/8"	6 1/2"	3 1/2"
16"	15 7/8"	6 1/2"	3 1/2"
18"	17 7/8"	6 1/2"	3 1/2"
20"	19 7/8"	6 1/2"	3 1/2"

(+/-) 1/8" Tolerance on all Sizes

Optional Features

Gauge Options: standard

26 ga

- 24 ga
- 22 ga
- 20 ga

Material Options:

- Aluminum
- Stainless steel

Construction Options:

- Extractor:
 - ___45° or ___90°
- Insulation Guard
- All seams sealed

Damper Options:

- BO3, Build-Out (2"), 3/8" square shaft, U-bolt, nylon bushings, locking quadrant, handle
- BO4, Build-Out (2"), 3/8" square shaft, U-bolt, nylon bushings, Rossi Everlock locking quadrant, handle



- BO3**
- 2" Build out
 - Locking Quadrant
 - 3/8" Aluminum Square Shaft
 - Nylon Bushing



- BO4**
- 2" Rossi (Everlock) Build out
 - Locking Quadrant
 - 3/8" Aluminum Square Shaft
 - Nylon Bushing