

SUBMITTAL DATA

Flexmaster U.S.A.® Connecting Sleeve

SHEET METAL FITTINGS



The Flexmaster U.S.A.® Connecting Sleeve (SL) is manufactured from 26 gauge, or heavier, galvanized steel to meet SMACNA and UMC Standards for commercial construction.

The SL should be installed using SMACNA installation standards.

Order Size	Diameter	Hole Cut Diameter	Length w/ and w/o Damper
4"	3 7/8"	5 3/4"	7 1/2"
5"	4 7/8"	6 3/4"	7 1/2"
6"	5 7/8"	7 3/4"	7 1/2"
7"	6 7/8"	8 3/4"	7 1/2"
8"	7 7/8"	9 3/4"	7 1/2"
9"	8 7/8"	10 3/4"	7 1/2"
10"	9 7/8"	11 3/4"	7 1/2"
12"	11 7/8"	13 3/4"	7 1/2"
14"	13 7/8"	15 3/4"	7 1/2"
15"	14 7/8"	16 3/4"	7 1/2"
16"	15 7/8"	17 3/4"	7 1/2"
18"	17 7/8"	19 3/4"	7 1/2"
20"	19 7/8"	21 3/4"	7 1/2"

(+/-) 1/8" Tolerance on all Sizes

Optional Features

Gauge Options: standard

26 ga

24 ga

22 ga

20 ga

Material Options:

Aluminum

Stainless steel

Damper Options:

BO3, Build-Out (2"), 3/8" square shaft, U-bolt, nylon bushings, locking quadrant, handle

BO4, Build-Out (2"), 3/8" square shaft, U-bolt, nylon bushings, Rossi Everlock locking quadrant, handle



BO3

- 2" Build out
- Locking Quadrant
- 3/8" Aluminum Square Shaft
- Nylon Bushing



BO4

- 2" Rossi (Everlock) Build out
- Locking Quadrant
- 3/8" Aluminum Square Shaft
- Nylon Bushing

Flexmaster U.S.A.®
5235 Ted Street
Houston, TX 77040 USA
Tel. +1.713.462.7694
Fax +1.713.939.8441
www.FlexmasterUSA.com
www.Masterduct.com

 **FLEXMASTER U.S.A.®**
A MASTERDUCT COMPANY